

DESIGNED TO **SIMPLIFY** LIFE
ENGINEERED TO **MAGNIFY** RESULTS



AGROLUX 60 | 4.80 | 90

For more information visit deutz-fahr.co.za or contact 0861 128 128

DEUTZ-FAHR SA (DF Africa (Pty) Ltd) is part of the Africom Group of Companies | africom.co

DEUTZ-FAHR is a trademark of  SDF



TECHNICAL DATA		AGROLUX					
		60		4.80		90	
		2WD	4WD	2WD	4WD	2WD	4WD
ENGINE							
Manufacturer		SDF 1000.3WTI		SDF 1000.4 WT		SDF 1000.4 WT	
Emissions		Tier 2		Tier 2		Tier 2	
Cylinders/Capacity	No./cm ³	3/3 000		4/4 000		4/4 000	
Naturally aspirated		•		•		-	
Max. Power	kW/hp	38.5/52		54.5/74		64.6/87	
Max. Engine speed (rated)	rpm	2 200		2 350		2 430	
Max. Torque	Nm	185.4		270		344	
Air cleaner with dust ejector		•		•		•	
Cooling liquid		•		•		•	
Under-hood silencer		vertical exhaust		vertical exhaust		•	
Fuel tank capacity	litres	70		70		90	
Biodiesel fuel	%	B100		B100		B100	
MECHANICAL GEARBOX							
Synchronised		•		•		•	
Electro-hydraulic engagement differential lock		-		-		•	
Number of speeds	n°	12FW + 3Rev		12FW + 3Rev		15+15	
Number of speeds with creeper		-		-		20+20	
Minimum speed/Minimum speed with creeper	km/h	-		-		0.508/3.729	
Maximum speed	km/h	30		30		40 - 30	
Hydrostatically operate self-adjusting dry clutch, single		•		•		•	
REAR P.T.O.							
Electro-hydraulic clutch with multiple discs		-		-		•	
PTO 540/540ECO		•		•		•	
FRONT AND REAR AXLE							
Mechanically operated		•		•		•	
Steering angle	degrees	55°		55°		55°	50°
BRAKES							
Oil immersed disc brakes and all 4WD braking		•		•		•	
Parking brake		•		•		•	
STEERING							
Hydrostatically steering		•		•		•	
HITCH							
Category		II		II		II	
Mechanical rear hitch		•		•		•	
Maximum lift capacity	kg	3 000		3 000		4 200	
HYDRAULIC SYSTEM							
Pump output (std)	litres/min.	33		42		54	
Auxiliary distributors	n°	1/2/4/6		1/2/4/6		2/4/6	
DRIVING POSITION							
Driver seat with mechanical suspension		•		•		•	
Analogue instrumentation		•		•		•	
DIMENSIONS AND WEIGHTS							
Standard rear tyres		16.9 - 28	16.9 - 28	16.9 - 30	16.9R30	460/85R30	460/85R34
Standard front tyres		7.50 - 16	12.9 - 20	7.50 - 16	11.2R24	7.50-18	420/85R24
Length	mm	3 315		3 445		4 075	
Width (min.-max.)	mm	1 985 - 2 285		1 838 - 2 325		2 050 - 2 250	
Wheelbase	mm	2 037	1 975	2 167	2 105	2 340	
Front track (min.-max.)	mm	1 740	1 750	1 780	1 750	1 600 - 2 100	
Rear track (min.-max.)	mm	1 840		1 902		1 600 - 2 100	
Ground clearance	mm	400		400		450	
Weight	kg	2 160	2 420	2 560	2 820	3 100	3 200