

DESIGNED TO **SIMPLIFY** LIFE
ENGINEERED TO **MAGNIFY** RESULTS



AGROPLUS F410 DT E3

For more information visit deutz-fahr.co.za or contact 0861 128 128

DEUTZ-FAHR SA (DF Africa (Pty) Ltd) is part of the Africom Group of Companies | africom.co

DEUTZ-FAHR is a trademark of  SDF



TECHNICAL DATA		AGROPLUS F410
ENGINE		
Emissions		Tier 3
Manufacturer		SDF 1000.4 WTI ER HRT
Cylinders/Capacity	No./cm ³	4/4 000
Turbo inter-cooler intake		•
Max. Homologated power (ECE R24.03)	kW/hp	62.5/85
Max. Engine speed (rated)	rpm	2 200
Max. Torque	Nm	345
Mechanical engine control		•
Cooling liquid		•
Under-hood silencer with side exhaust		•
Fuel tank capacity	litres	55
Biodiesel fuel	%	B100
MECHANICAL GEARBOX		
Synchronised, 5 gear gearbox with creeper/and splitter		30F + 15R
Max. Speed	km/h	40
Mechanical shuttle		•
REAR P.T.O.		
Mechanical dry clutch		•
Mechanical operation		•
Speed	rpm	540/540 ECO/1 000
FRONT AND REAR AXLE		
Front wheel drive mechanically operated/Electro-hydraulic operated		•
Mechanically operated differential lock/ Electro-hydraulic		•
Steering angle	degrees	55°/60°
BRAKES		
Hydraulic trailer braking		•
Braking system on front and rear axles		•
STEERING		
Hydrostatic steering		•
HYDRAULIC SYSTEM		
Pump output	litres/min.	54
Mechanical rear power lift	kg	3 000 (full travel at hitch balls)
Max. Lift capacity		•
Hydraulic auxiliary control valves	No. of ways	3/4/6
Mechanical RH link arm and stabilisers		•
DRIVING POSITION		
Lateral geara leavers		•
Driver seat with mechanical adjustment		•
Instrumentation analogue and digital		•
DIMENSIONS AND WEIGHTS		
Max. Length with link arms	mm	4 315
Max. Height of cab	mm	2 295
Ground clearance (240/70R16)	mm	238
Wheelbase	mm	1 990
Front track max	mm	1 120 - 1 320
Rear track min. - max.	mm	1 050 - 1 420
Weight with safety frame	kg	2 900